

SG6H Filter Operation

Filtering


1

<p>1</p>		<p>3</p>		
<p>Turn Fryer Off</p>	<p>Drain Tank</p>	<p>Turn Pump On</p>	<p>Push Flow Selector In</p>	<p>Brush Bottom Clean</p>
			<p>9</p>	
<p>Rinse Tank</p>	<p>Close Drain</p>	<p>Refill Tank</p>	<p>Turn Pump Off</p>	

SG6H Filter Operation




Polishing

2

<p>1</p> <p>Filter Oil Using Procedure</p> <p>1</p>	<p>2</p>  <p>Clean Out Pan</p>	<p>3</p>  <p>Wash Parts</p>	<p>4</p>  <p>Thoroughly DRY ALL PARTS</p>	<p>5</p>  <p>Reassemble Pan</p>
<p>6</p>  <p>Add Filter Aid To Cracklin Basket</p>	<p>7</p>  <p>Replace Pan</p>	<p>8</p>  <p>Turn Off Fryer</p>	<p>9</p>  <p>Drain Tank</p>	<p>10</p>  <p>Turn On Pump</p>
<p>11</p>  <p>Pull Flow Selector Out</p>	<p>12</p> <p>Allow Oil To Re-circulate For 30 Minutes</p>	<p>13</p>  <p>Close Drain And Push Flow Selector In</p>	<p>14</p>  <p>Refill Tank</p>	<p>15</p>  <p>Turn Pump Off</p>

End of Day Filter Pan Clean Up

3

<p>1</p>  <p>Clean Out Pan</p>	<p>2</p>  <p>Wash Parts</p>	<p>3</p>  <p>Thoroughly DRY ALL PARTS</p>	<p>4</p> <p>All Filter Parts Must Be Allowed To Air Dry Overnight Before Use.</p>
--	---	---	--

